

## Declaration of performance

No. NORDIC ALU window

1. Product type: **NORDIC ALU (window)**.
2. Identification no.: (Acc. Order No.: )
3. Purpose: For commercial and private buildings (except critical zones).
4. Manufacturer: **UAB HCTC, Pramonės str. 97, Vilnius, LT-11115**.
5. –
6. System of assessment and verification of performance: **3**.
7. Harmonised standard: **EN 14351-1: 2006+A2:2016**.
8. The notified body:
  - Danish Technological Institute, Teknologiparken, Kongsvang Alle 29, DK-8000 Aarhus C. EU Notified Body number: 1235 ;
  - Institute of Architecture and Construction of Kaunas University of Technology, Laboratory of Building Thermal Physics, Tunelio str. 60, LT-44405, Kaunas, Lithuania. Notified Body number: 2018 .
9. Declared performance:

Essential characteristics	Performance	Harmonizes technical specification
Resistance against wind load	<b>3C</b>	<b>EN 14351-1:2006+A2:2016</b>
Water tightness	<b>AE1200</b>	<b>EN 14351-1:2006+A2:2016</b>
Sound insulation	<b>33 (-1;-5) dB</b>	<b>EN 14351-1:2006+A2:2016</b>
Thermal transmission coefficient	<b>0.75*</b>	<b>EN 14351-1:2006+A2:2016</b>
Air permeability	<b>4</b>	<b>EN 14351-1:2006+A2:2016</b>
Radiation properties		
-Light transmittance factor	<b>0,74</b>	<b>EN 14351-1:2006+A2:2016</b>
-Total solar energy transmittance	<b>0,53</b>	<b>EN 14351-1:2006+A2:2016</b>
Dangerous substances	<b>None</b>	<b>EN 14351-1:2006+A2:2016</b>

NPD – No performance determined;

\*- where detailed calculation of the heat from are specific building is required, the manufacturer shall provide accurate and relevant, calculated or tested thermal transmittance values (design values).

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature